


NO.12 PORCELAIN™



COLORS / SIZES

SUPER WHITE NB50



AVORIO NB51



BEIGE NB52



SILVER GRAY NB53



ASH GRAY NB54



BLUE NB55




GRIGIO NB56



TOBACCO NB57




NERO NB58




SUPER BLACK NB59



- 12" x 24" available in all colors MATTE/POLISHED
- 24" x 24", 6" x 24", 12" x 12" available in all colors MATTE
- 24" x 24", 6" x 24", 12" x 12" POLISHED Special Order only



2" x 2" MOSAIC MATTE



13" x 19" RANDOM LINEAR MOSAIC MATTE



4" x 12" BULLNOSE MATTE



6" x 12" COVE BASE MATTE



1" x 6" COVE BASE CORNER

All mosaics and trim are available in all colors. Shown in ASH GRAY NB54.

SPECIFICATION

	COLOR VARIATION	DCOF	BREAKING STRENGTH	MOHS	WATER ABSORPTION	CHEMICAL RESISTANCE	ABRASION RESISTANCE	THERMAL SHOCK RESISTANCE	FROST RESISTANCE
U.S. INSPECTION STANDARDS	N/A	ANSI A326.3	ASTM C648	Scratch Hardness 1 - 10	ASTM C373	ASTM C650	Class 0 to 5	ASTM C484	ASTM C1026
FACTORY TEST RESULT	V1	≥ 0.42	> 450 lbs	7.0	< 0.5%	Resistant	Dependent on Color	Resistant	Resistant

APPLICATIONS

	TARGET DCOF	SUITABLE
DRY & LEVEL - INTERIOR	--	●
WET & LEVEL - INTERIOR	≥ 0.42	●
COMMERCIAL DINING AREAS	≥ 0.50	●
EXTERIOR (Pool Decking & Other Wet Areas with Minimal Footwear)	≥ 0.60	● Textured Only
COVERED EXTERIOR	≥ 0.60	○
RAMP & INCLINES	≥ 0.65	○

OTHER APPLICATIONS

	SUITABLE
WALLS/BACKSPLASHES	●
COUNTERTOPS	●
POOL LININGS	●